




# MegaCode Kid

Preventative Maintenance Kit











## Items Included

Before you install this Preventative Maintenance Lite Kit, please visit <u>www.laerdal.com/laerdalpmkit</u> and watch the instructions.







#### Remove the torso skin

Detach and unpeel the torso skin.

#### Replace the defibrillation studs

- 1. Remove the defibrillation studs located on the chest and lower left torso.
- 2. Mount the new defibrillation studs and washers.

## Replace the ECG studs

- 1. Remove the four ECG studs located on the shoulders and lower torso.
- 2. Mount the new ECG studs and washers.

## Replace the lung tubes

- 1. Remove the white plug securing the lungs on the chest plate.
- 2. Remove the pin from the washer.
- 3. Discard the pin, set the washer aside.
- 4. Remove the stomach and put it aside without disconnecting the wires.
- 5. Remove the chest plate and put it aside.
- 6. Disconnect the lung tubes connecting the airways to the lungs.
- 7. Connect the new lung tubes to the airways.
- 8. Place the chest plate on the torso.
- 9. Insert the lung tubes in their housings on the chest plate and guide them around it.



- Make sure the tubes are not pinched by the chest plate.
- Make sure the compression spring is correctly positioned.

## Replace the lungs



There are two sets of lungs in the kit, use the same ones as those currently installed.

- 1. Take the new lungs and flatten them on the chest plate.
- 2. Connect the lung tubes to the lungs.
- 3. Take a new white pin and the old washer and assemble them.
- 4. Use the white plug to secure the lungs on the chest plate.
- 5. Place the stomach back on the torso.







## Arms and Legs

## Replace the lower right leg

- 1. Unscrew the lower right leg and remove it.
- 2. Take the new lower right leg and mount it on the leg.
- 3. Screw the lower right leg on the leg.
- 4. Check that it moves freely by bending the knee.

## Replace the lower right leg

- 1. Unscrew the lower right leg and remove it.
- 2. Take the new lower right leg and mount it on the leg.
- 3. Screw the lower right leg on the leg.
- 4. Check that it moves freely by bending the knee.

## Replace the deltoid IM pads

- 1. Remove the deltoid IM pads located on each shoulder.
- 2. Insert the new deltoid IM pads.

#### Replace the right arm skin and veins

- 1. Carefully cut the right arm skin and peel it off.
- 2. Remove the veins.
- 3. Clean the arm to remove any dust or left over material.
- 4. Place the new veins in the hand and between the fingers.
- 5. Apply small amounts of super glue where the veins touch the hand.
- 6. Press and hold the veins in place until the glue sets.
- 7. Repeat the action on the other side of the arm.
- 8. Lubricate the inside of the new arm skin with liquid soap.
- 9. Put the arm skin on the manikin's right arm.



If needed, apply more liquid soap to make the arm skin slide on more easily.





